

EQUIPEMENT STANDARD

- Easy to install on all machines: drilling, tapping & cut-off machines, etc.
- Installation : right or left side of the machine
- Display and input on 7" colour touch screen (in French)
- Setting by entering the measure or by selecting from 12 memories (expandable to 99)
- Resolution : 0.1 mm
- Precision : 1/10 mm on high precision rack
- Movement speed : 400 mm/s (*configurable*)
- Automatic blocking in position
- Configurable automatic withdrawal
- Stroke lengths : 4000 to 6000 mm
- **Other lengths on request**
- Usable width : 200 or 400
- **Other widths on request**
- Rollers Ø 40 mm STEEL or PVC (to be specified when ordering)
3 at 200 mm pitch, the rest at 400 mm pitch
- Protective metal sheet between rollers
- Load : 60 Kg/m
- Adjustable height: 740 to 1000 mm



Remote console



Screen of TYRObut



- 1 - Visual movement
- 2 - Memory N°
- 3 - Memories scrolling
- 4 - Memorised measure
- 5 - Actual position
- 6 - Withdrawal key
- 7 - Step by step movement value
- 8 - Step by step movement & direction

Standard size : other sizes on request		
Working stroke	Width : 200 mm Rollers : Ø 40 mm Steel or PVC	Width : 400 mm Rollers : Ø 40 mm Steel or PVC
3000 mm	YES	YES
4000 mm	YES	YES
6000 mm	YES	YES
7000 mm	YES	YES
Machinery accessories :		
Front foot for free-standing mounting	YES	YES
Rope pull emergency stop switch	YES	YES
Remote console	YES	YES